

TX-5353SW230C30F14-03H952770

PRODUCT SPECIFICATION (R&D version)

Features:


- Excellent heat dissipation. Heat from LED chip operating under 6A.
- Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- High luminous output.
- No UV.
- Encapsulated materials are environmentally certified and meet environmental requirements.

CM

á

Part No.	TX-5353SW230C30F14-03H952770	Spec No.	R&D version	Page	1 of 4
----------	------------------------------	----------	-------------	------	--------

Package Dimensions:



TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

TYANSHINE 广州市添鑫光电有限公司
Guangzhou Tianxin Photoelectric Co.,Ltd

Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	v	If=5.5A	S	—	15000	—	lm
			W	—	20000	—	
Forward Voltage	V _f		S	39	42	45	V
			W	39	42	45	
Correlated Colour Temperature	CCT		S	2600	2700	2740	K
			W	6600	7000	7200	
Viewing Angle at 50° IV	2 1/2		S	—	115	—	Deg
			W	—	115	—	
Reverse Current	I _R	—	—	—	—	—	μA
Color Rendering Index	Ra	If=5.5A	S	95	—	—	—
			W	95	—	—	

Notes:

- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $2\frac{1}{2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance: $\pm 15\%$.
- 4.Forward voltage measurement tolerance: $\pm 3\%$.
- 5.Ra measurement tolerance: 2.

Part No.	TX-5353SW230C30F14-03H952770	Spec No.	R&D version	Page	4 of 4
----------	------------------------------	----------	-------------	------	--------